

## 17. Water and Waste Management / Landfill (Methane Recovery)

### 1. Typical Project Outline

- Recovery of landfill gas (LFG) from landfills or waste disposal sites.

### 2. Applicability

- (1) LFG recovery from disposal sites where anaerobic and aerobic treatments are occurred.
- (2) Recovered LFG are used for direct power generation or thermal energy purpose.
- (3) Landfills completed or disposal sites in use are targeted.

### 3. Methodology of Emission Reduction Calculation

The emission reduction from the project activity is determined as the differences between the GHG emissions of baseline scenario (LFG are emitted to atmosphere without recovery) and project scenario (recovery and application of LFG)<sup>1</sup>.

Details of sources of each data in the following formulae are provided in “4. Data and Parameters for the Estimation”.

$$ER_y = BE_y - PE_y$$

$ER_y$  : Emission reduction through the projet in year y (t-CO<sub>2</sub>e/y)

$BE_y$  : GHG emission from the baseline scenario in year y (t-CO<sub>2</sub>e/y)

$PE_y$  : GHG emission from the project scenario in year y (t-CO<sub>2</sub>e/y)

#### (1) Calculation of Baseline Emission

The baseline emissions are comprised of uncaptured methane emitted to the atmosphere from landfill sites and the CO<sub>2</sub> emissions from generation of electric power and/or thermal energy that will be replaced by electricity generated or thermal energy by LFG-fueled power plants or boilers.

$$BE_y = (MD_{PJ,y} - MF_{BL,y}) \times GWP_{CH_4} + BE_{EN,y}$$

$MD_{PJ,y}$  : Methane recovered and destroyed by the project (t-CH<sub>4</sub>/y) (=methane emission from landfill sites in the baseline)

$MF_{BL,y}$  : Methane quantity to be flared as required by National Regulations before the project starts (t-CH<sub>4</sub>/y). It shall be “0” as developing countries have very limited regulations on CH<sub>4</sub> emissions.

$GWP_{CH_4}$  : Methane Global Warming Potential (=25 t-CO<sub>2</sub>/t-CH<sub>4</sub>)

$BE_{EN,y}$  : Baseline emissions from generation of energy displaced by the project activity (t- CO<sub>2</sub>/y)

#### Determination of $MD_{PJ,y}$ :

Methane quantity from landfill (CH<sub>4</sub> quantity recovered and destroyed by the project) shall be determined by monitoring the quantity of degradable organic carbon reclaimed in the landfill in consideration of decomposition rate.

$$MD_{PJ,y} = \eta_{PJ} \times BE_{CH_4,SWDS,y}$$

$$BE_{CH_4,SWDS,y} = \varphi \times (1 - OX) \times 16/12 \times F \times MCF_{BL} \times \sum_{x=1}^y \sum_j \{W_{j,x} \times DOC_{f,j} \times DOC_j \times e^{-k_j(y-x)} \times (1 - e^{-k_j})\}$$

<sup>1</sup> The target year shall be a representative year under average operation or an annual average of multiple years.

## 17. Water and Waste Management / Landfill (Methane Recovery)

$\eta_{PJ}$	: Efficiency of LFG recovery (%)
$\varphi$	: Model correction factor to account for model uncertainties
OX	: Oxidation rate
F	: Fraction of CH <sub>4</sub> in LFG
$DOC_{fj}$	: Fraction of degradable organic carbon (DOC) that can decompose in the waste type j
MCF	: CH <sub>4</sub> correction factor
$W_{j,x}$	: Annual quantity of the waste type j disposed in the landfill site in year x (t/y)
$DOC_j$	: Fraction of degradable organic carbon (by weight) in the waste type j
x	: Years in the time period in which waste is disposed at the SWDS, extending from the first year in the time period (x =1) to year y (x = y).
y	: Year of the period for which waste is disposed at the SWDS and methane emissions are calculated
$k_j$	: Decay rate for the waste type j (unit/y)
j	: Type of residual waste or types of waste in the MSW
e	: Base of natural logarithm

$W_{j,x}$  is determined as follows.

$$W_{j,x} = W_x \times w_j$$

$W_x$  : Annual quantity of the waste disposed in the landfill site in year x (t/y)

$w_j$  : Weight fraction of the waste type j in the waste disposed (weight basis) (%)

### Determination of $MF_{BL,y}$ :

It is determined by multiplying the methane quantity from landfill with the fraction of decomposed and combusted.

$$MF_{BL,y} = MD_{PJ,y} \times AF$$

$MD_{PJ,y}$  : Methane quantity recovered from landfill by the project

AF : Methane fraction required for flare and combustion under the National Regulations before the project starts.

It will be zero as developing countries mostly have no this regulation.

### Determination of $BE_{EN,y}$ :

It is determined by the quantity of electricity and thermal energy generated after by the project and corresponding CO<sub>2</sub> emission factors.

$$BE_{EN,y} = BE_{elec,y} + BE_{heat,y} = EG_{PJ,y} \times EF_{elec} + HG_{PJ,y} / \eta_{BL} \times EF_{fuel,BL} \div 10^3$$

$BE_{elec,y}$  : Baseline emissions to generate the same amount of electricity generated by project activity (t-CO<sub>2</sub>/y)

$BE_{heat,y}$  : Baseline emissions to generate the same amount of thermal energy produced by the project activity (t-CO<sub>2</sub>/y)

$EG_{PJ,y}$  : Amount of electricity generated by the project (MWh/y)

## 17. Water and Waste Management / Landfill (Methane Recovery)

- $EF_{elec}$  : CO<sub>2</sub>emission factor of the electricity (t-CO<sub>2</sub>/MWh)  
 $HG_{PJ,y}$  : Amount of thermal energy generated by the project (TJ/y)  
 $\eta_{BL}$  : Energy efficiency of the boiler/air heater used in the baseline scenario to generate the thermal energy.  
 It will be “1” as a conservative value.  
 $EF_{fuel,BL}$  : CO<sub>2</sub> emission factor of the fuel used in the baseline scenario (kg-CO<sub>2</sub>/TJ)

### (2) Calculation of Project Emission

The project emissions is comprised of the GHG emission from electricity and fuel consumption in the LFG recovery plants or power generating plants after the project starts as follows;

$$PE_y = PE_{EC,y} + PE_{FC,y}$$

- $PE_y$  : GHG emission from the project in year y (t-CO<sub>2</sub>/y)  
 $PE_{EC,y}$  : GHG emission from electricity consumption by the project in year y (t-CO<sub>2</sub>/y)  
 $PE_{FC,y}$  : GHG emission from fossil fuel consumption by the project in year y (t-CO<sub>2</sub>/y)

#### Determination of $PE_{EC,y}$ :

It is determined as follows.

$$PE_{EC,y} = EC_{PJ,y} \times EF_{elec}$$

- $EC_{PJ,y}$  : Amount of electricity consumption by the project (MWh/year)  
 $EF_{elec}$  : CO<sub>2</sub>emission factor of the electricity (t-CO<sub>2</sub>/MWh)

#### Determination of $PE_{FC,y}$ :

It is determined as follows.

$$PE_{FC,y} = \sum_i (FC_{PJ,i,y} \times NCV_{fuel,i} \times EF_{fuel,i} \div 10^6)$$

- $FC_{PJ,i,y}$  : Amount of fuel consumption by the project (t/year)  
 $NCV_{fuel,i}$  : Net calorific value of the fuel i applied in the project (TJ/Gg = TJ/kt)  
 $EF_{fuel,i}$  : CO<sub>2</sub> emission factor of the fuel i applied in the project (kg-CO<sub>2</sub>/TJ)

### 4. Data and Parameters for the Estimation

Data	Description	Data Sources	
		For baseline emission calculation	For project emission calculation
$\eta_{PJ}$	Efficiency of LFG recovery (%)	0.5 (Default value: AMS-III.G: Landfill methane recovery)	N/A

### 17. Water and Waste Management / Landfill (Methane Recovery)

$\phi$	Model correction factor to account for model uncertainties	0.75 (Default value: CDM Methodological Tool: Emissions from solid waste disposal sites)	N/A
F	Fraction of CH <sub>4</sub> in LFG	0.5 (Default value <sup>2</sup> )	N/A
OX	Oxidation rate	Managed covered with oxidising material such as soil and compost: 0.1 Other landfill sites: 0 (Default value <sup>3</sup> )	N/A
DOC <sub>f,j</sub>	Fraction of degradable organic carbon (DOC) that can decompose in the waste type j	Default value of IPCC (Table 8, Appendix)	N/A
DOC <sub>j</sub>	Fraction of degradable organic carbon (by weight) in the waste type j (%)	Default value of IPCC (Table 8, Appendix)	N/A
MCF	CH <sub>4</sub> correction factor	Default value of IPCC (Table 9, Appendix)	N/A
W <sub>x</sub>	Annual quantity of the waste disposed in the landfill site in year x (t/y)	Choose one of the following options considering availability: i) Result of a feasibility study or other studies ii) Interview with disposal site managers iii) Estimation by truck scaling * Use planned average amount of waste disposal after the project starts.	N/A
w <sub>j</sub>	Weight fraction of the waste type j in the waste disposed (weight basis) (%)	Choose one of the following options considering availability: i) Result of a feasibility study or other studies ii) Result of a study on waste composition of the target city iii) Sampling survey at the landfill site iv) IPCC default value (waste composition by regions <sup>4</sup> ) * Use planned average value after the project starts.	N/A
k <sub>j</sub>	Decay rate for the waste type j (unit/y)	Default value of IPCC (Table 10, Appendix)	N/A
EG <sub>PJ,y</sub>	Amount of electricity generated by the project (MWh/y)	A planned value	N/A
HG <sub>PJ,y</sub>	Amount of thermal energy generated by the project (TJ/y)	A planned value	N/A

<sup>2</sup> 2019 Refinement to the 2006 IPCC Guidelines for National Greenhouse Gas Inventories, Volume 5: Waste, p.3.14

<sup>3</sup> 2019 Refinement to the 2006 IPCC Guidelines for National Greenhouse Gas Inventories, Volume 5: Waste, Table 3.2

<sup>4</sup> 2019 Refinement to the 2006 IPCC Guidelines for National Greenhouse Gas Inventories, Volume 5: Waste, Table 2.3 (Updated)

## 17. Water and Waste Management / Landfill (Methane Recovery)

EF <sub>elec</sub>	In the case of grid connection: CO <sub>2</sub> emission factor of the grid electricity (t-CO <sub>2</sub> /MWh)	A default value (Table 3, “Energy Consumption”, Appendix) If there is no default value applied or if there is another appropriate value, that value may be used.	
	In the case of captive power generation or mini-grid: CO <sub>2</sub> emission factor of the diesel power generation (t-CO <sub>2</sub> /MWh)	A default value (Table 4, Appendix) If there is no default value applied or if there is another appropriate value, that value may be used.	
NCV <sub>fuel,i</sub>	Net calorific value of the fuel i applied in the project (TJ/Gg = TJ/kt)	N/A	An IPCC default value (Table 1, Appendix) If there is no default value applied or if there is another appropriate value, that value may be used.
EF <sub>fuel,BL</sub>	CO <sub>2</sub> emission factor of the fuel used in the baseline scenario (kg-CO <sub>2</sub> /TJ)	An IPCC default value (Table 2, Appendix) If there is no default value applied or if there is another appropriate value, that value may be used.	
EF <sub>fuel,i</sub>	CO <sub>2</sub> emission factor of the fuel i applied in the project (kg-CO <sub>2</sub> /TJ)	An IPCC default value (Table 2, Appendix) If there is no default value applied or if there is another appropriate value, that value may be used.	
EC <sub>PJ,y</sub>	Amount of electricity consumption by the project (MWh/year)	N/A	A planned value
FC <sub>PJ,i,y</sub>	Amount of fuel consumption by the project (t/year)	N/A	A planned value

### 5. Others

#### (1) Project Boundary

The project boundary is the site where the project activity is being done, where the gas is captured and destroyed/used.

#### (2) Leakage

Construction of power plants, replacement of facility: the indirect emissions potentially leading to leakage due to activities such

## 17. Water and Waste Management / Landfill (Methane Recovery)

as product manufacturing or materials transport in consideration of Life Cycle Assessment, LCA of disposal of waste at a solid waste disposal site. The contribution of this emission is relatively small and negligible compared with the GHG emission reduction after the project starts. The methodology ignores the leakage because ACM0001 also ignores it.

### (3) Comparison with existing CDM methodologies

The logic of emission reduction calculation in the methodology is almost the same as that of the ACM 0001. However, this methodology simplified the methodology by using default values as more as possible. Moreover, there is no limitation for the emission reduction in the methodology like the small-scale CDM methodologies did.

Also, "Guideline for National Greenhouse Inventory" (IPCC, 2006) explains that N<sub>2</sub>O is not important and the estimation method has not been established, so it has not been added to the calculation method.

### (4) Revision history

Version	Year/Month	Revisions
2.0	March 2014	<ul style="list-style-type: none"> <li>Added default values for combined margins and operating margins of CO<sub>2</sub> emission factors of electricity</li> </ul>
3.0	September 2019	<ul style="list-style-type: none"> <li>Prioritized the use of default values</li> <li>Added instructions not to consider N<sub>2</sub>O emissions</li> </ul>
4.0	March 2023	<ul style="list-style-type: none"> <li>In the description of the calculation method and necessary data of baseline emissions, the words "before project implementation" was revised to use "the baseline scenario". The baseline scenario is the scenario that would have occurred in the absence of the project, such as continuation of the pre-project conditions.</li> <li>Deleted the column "Ex-post" in "4. Data and Parameters Estimated and Need Monitoring": current version of Climate-FIT aims to quantify GHG emission reductions in the "planning phase").</li> </ul>
5.0	March 2024	<ul style="list-style-type: none"> <li>The oxidation factor (OX) was set to the default value of IPCC 2019 (2019 Refinement to the 2006 IPCC Guidelines for National Greenhouse Gas Inventories).</li> <li>The "Fraction of degradable organic carbon (DOC<sub>tj</sub>)" can be set for each waste type according to IPCC2019.</li> <li>The source of the percentage of CH<sub>4</sub> in LFG (F) was modified to apply the value of IPCC2019.</li> <li>Removed subscript y of each parameter, which implies monitoring for each year (since Climate-FIT is intended to quantify GHG emission reductions in the "planning phase").</li> <li>Revised the "Data sources" for W<sub>x</sub> and w<sub>j</sub> to be more accessible based on the actual situation in the target countries.</li> <li>The "Description" (name of parameter) for W<sub>j,x</sub>, W<sub>x</sub>, and w<sub>j</sub> were modified.</li> </ul>