MONITORING FORM

If environmental reviews indicate the need of monitoring by JICA, JICA undertakes monitoring for necessary items that are decided by environmental reviews. JICA undertakes monitoring based on regular reports including measured data submitted by the project proponent. When necessary, the project proponent should refer to the following monitoring form for submitting reports.

When monitoring plans including monitoring items, frequencies and methods are decided, project phase or project life cycle (such as construction phase and operation phase) should be considered.

1. Responses/Actions to Comments and Guidance from Government Authorities and the Public

Monitoring Item	Monitoring Results during Report Period
ex.) Responses/Actions to Comments and	April 2017 – June 2017
Guidance from Government Authorities	

2. Mitigation Measures

The summary of the Environmental Monitoring is shown below.

[Construction Phase]

[Construction	V		
Item '	Parameter	Frequency and Duration	Locations(At least)
Air	PM ₁₀	2×24hours Twice/month During entire civil construction stage or even later, if directed by DMRC	20 locations
Water	Groundwater quality (IS 10500:1991)	Once/6months During entire civil construction stage or even later, if directed by DMRC	20 locations
Noise	Noise Level (Leq and Lmax)	24hours Once/week During entire civil construction stage or even later, if directed by DMRC	30 locations
Vibration .	Vibration (RMS)	24hours Once/week During entire civil construction stage or even later, if directed by DMRC	10 locations
Şoil	Heavy Metal	Once/6moths During entire civil construction stage	In each Underground Construction Contract
Ecology	Felled and planted trees	Once a year till all trees that were to be planted by Delhi Government on behalf of DMRC, are planted	

3

-3

Item	Parameter	Frequency and Duration	Locations		
Air	PM ₁₀	2×24hours Once/month For 3years	10 locations		
Water	Effluent	Once/4months For 3years	3 locations(Depot)		
	Groundwater quality (IS 10500:1991)	Once/year For 3years	3 locations(Depot)		
Noise	Noise Level (Leq)	24hours Once/year For 3years	15 locations (Sensitive Receptors along the elevated section)		
Vibration •	on Vibration level 24hours Once/year For 3years		15 locations (Sensitive Receptors along the elevated and underground section)		
Ecology	Bird Strike	4times/year(If no bird hit is reported in this duration, then this monitoring may be discontinued, else it will continue). From the beginning, DMRC will instruct its train operator to compulsorily blow the horn while on the bridge across the Yamuna.	On the DMRC Yamuna bridge near Okhla Bird Sanctuary		

2.1 During Construction

Air Quality (Ambient Air Quality)

Date: April 2017

2 2 2

9 9

や オマ かっ つっ つっ つっ

Location: CC-04 (Azadpur) (Underground)

Item	Ųnit	Measured Value (Mean)	Measured Value (Max.)	Country's Standards	Referred Internation al Standards	Remarks (Measurement Point, Frequency, Method, etc.)
PM ₁₀	μg/m³	Azadpur – 221.1 Rameshwar nagar – 195	223.6 197.4	100 (24hours) (CPCB)	<u>-</u>	2×24hours Twice/month During entire civil construction stage or even later, if directed by DMRC

Date: May 2017

Location: CC-79 (Okhla Phase-3) (Elevated)

Item	Unit	Measured Value (Mean)	Measured Value (Max.)	Country' s Standard s	Referred Internation al Standards	Remarks (Measurement Point, Frequency, Method, etc.)
PM ₁₀	μg/m³	Activity Area – 153 Batching Plant – 161.5	157 169	100 (24hours) (CPCB)	-	2×24hours Twice/month During entire civil construction stage or even later, if directed by DMRC

Date: May 2017 Location: Janakpuri- Dabri mod CC-34 (Underground)

Item	Unit	Measured Value (Mean)	Measured Value (Max.)	Country 's Standar ds	Referred Internation al Standards	Remarks (Measurement Point, Frequency, Method, etc.)
PM ₁₀	hā/m³	Janakpuri – 140 Dasrathpuri – 154 Dabri Mor – 139.5	149 157 146	100 (24hours) (CPCB)	-	2×24hours Twice/month During entire civil construction stage or even later, if directed by DMRC

Location: MIE-City Park CC-43 (Elevated)

Date: April 2017

Item	Unit	Measured Value (Mean)	Measured Value (Max.)	Country 's Standar ds	Referred Internation al Standards	Remarks (Measurement Point, Frequency, Method, etc.)
PM ₁₀	µg/m³	MIE-187 Bus Stand- 197 City Park- 211.5 Casting Yard – 188.5	195 213 219 209	.100 (24hours) (CPCB)	-	2×24hours Twice/month During entire civil construction stage or even later, if directed by DMRC

Ground Water Quality (Drinking Water Quality: IS 10500:1991)

Date: May 2017

Location: Bahadurgarh Casting yardCC-43 (Elevated)

Item	Unit	Measure d Value (Mean)	Measured Value (Max.)	Country's Standards	Referred Internation al Standards	Remarks (Measurem ent Point, Frequency, Method, etc.)
Color,Hazen units,Max			Colourless	5(25)	-	20 locations Once/6
Odour	-	,	Unobjection able	Unobjectiona ble	-	months
Taste			Agreeable	Agreeable	-	During
Turbidity,NTU, Max	•	, 74	1.65	5(10)	_	entire civil construction
pH Value	· -		7.73	6.5-8.5	-	stage or
Total Hardness (as CaCO ₃), Max	mg/l		349*	300(600)	•	even later, if directed by DMRC
Iron(as Fe) ,max	mg/l		0.09	0.3(1.0)	-	u .
Chloride(as CI), Max	mg/l		179	250(1000)	-	-
Residual free Chlorine, Min	mg/l		Nil	0.2	-	
Fluoride(as F), Max	mg/l		3.26*	1.0(1.5)	-	
Dissolved solids, Max	mg/[2719*	500(2000)	-	
Calcium(as Ça), Max	mg/l			75(200)	· <u>-</u>	
Magnesium(as Mg), Max	mg/l		- = = = = = = = = = = = = = = = = = = =	30(100)	-	·
Copper(as Cu), Max	mg/l		BDL	0.05(1.5)	-	

Manganese(as Mn), Max	mg/l		BDL	0.1(0.3)	-	
Sulphate(as SO ₄), Max	mg/l		259*	200(400)	-	
Nitrate(as NO ₂), Max	mg/l		61.3*	45(100)	•	
Phenolic compounds (as C ₆ H ₅ OH),Max	mg/l		BDL	0.001(0.002)	- .	
Mercury(as Hg), Max	mg/l	,	BDL	0.001	-	
Cadmium(as Cd), Max	mg/l		BDL.	0.01	_	
Selenium(as Se), Max	mg/l		BDL	0.01	-	
Arsenic(as As), Max	mg/l		BDL	0.05	_	
Cyanide(as CN), Max	mg/l		BDL	0.05		
Lead(as Pb), Max	mg/l		BDL	0.05	-	
Zinc(as Zn), Max	mg/l		0.04	5(15)	-	1
Anionic Detergents (as MBAS),Max	mg/l	-	BDL	0.2(1.0)	· -	
Chromium (as Cr6 ⁺),Max	mg/l		BDL	0.05	_ `	
Polynuclear aromatic hydrocarbons(as PAH),Max	mg/l		BDL	-	-	_
Mineral Oil	mg/l			0.01		
Pesticides, Max	mg/l			Absent	-	
Radioactive Materials, Max a) Alpha emitters	Bq/I		7-140	-(0.1)	-	
Radioactive Materials, Max b) Beta emitters	Pci/l			-(1)	- -	
Alkalinity, Max	mg/l	······································	141.3	200(600)	-	•
Aluminum(as Al), Max	mg/l		BDL	0.03(0.2)	-	•
Boron,Max	mg/l		BDL	1(5)	-	

Location: Ramp CC-66 (Underground)

Date: April 2017

DAPPRICATOR TO PROPERTO PROPERTOR

ltem	Unit	Measure d Value (Mean)	Measured Value (Max.)	Country's Standards	Referred Internation al Standards	Remarks (Measurem ent Point, Frequency, Method, etc.)
Color,Hazen units,Max			Colourless	5(25)	-	20 locations Once/6
Odour	-		Unobjection able	Unobjection able	-	months
Taste	-		Agreeable	Agreeable	**	During
Turbidity,NTU, Max	-		1.87	5(10)	•	entire civil construction
рН Value	-		7.85	6.5-8.5	-	stage or
Total Hardness (as CaCO₃), Max	mg/l		287	300(600)	_	even later, if directed by DMRC
Iron(as Fe) ,max	mg/l		.14	0.3(1.0)	_	
Chloride(as CI),	mg/l		1 59	250(1000)		
Max Residual free Chlorine, Min	mg/l		Nil	0.2	-	
Fluoride(as F),	mg/l		2.56*	1.0(1.5)	_	·
Dissolved solids, Max	mg/l		1798	500(2000)	•	;
Calcium(as Ca), Max	mg/l		• ••	75(200)	-	
Magnesium(as Mg), Max	mg/l		,	30(100)	_	
Copper(as Cu), Max	mg/l		BDL	0.05(1.5)		
Manganese(as Mn), Max	mg/l		BDL	0.1(0.3)	<u>.</u>	
Şulphate(as SO₄), Max	mg/l		97	200(400)	-	
Nitrate(as NO ₂), Max	mg/l		61.7	45(100)	-	
Phenolic compounds (as C ₆ H ₅ OH),Max	mg/l	,	BDL	0.001(0.002)	-	
Mercury(as Hg),	mg/l		BDL	0.001	-	
Cadmium(as Cd),	mg/l		BDL	0.01	-	
Selenium(as	mg/l	 , 	BDL	0.01	# · · · · · · · · · · · · · · · · · · ·	

		 			prince
Şe), Max					
Arsenic(as As),	mg/l	BDL	0.05		·
Cyanide(as CN), Max	mg/l	BDL	0.05	-	
Léad(as Pb), Max	mg/l	BDL	0.05	-	
Zinc(as Zn), Max	mg/l	1.68	5(15)	_	
Anionic Detergents (as MBAS),Max	mg/l		0.2(1.0)	•	,
Chromium (as Cr6⁺),Max	mg/l		0.05 .	-	
Polynuclear aromatic hydrocarbons(as PAH),Max	mg/l	BDL	-	-	
Mineral Oil	mg/l		0.01	-	
Pesticides, Max	mg/l		Absent	-	
Radioactive Materials, Max c) Alpha emitters	Bq/l		-(0.1)		
Radioactive Materials, Max d) Beta emitters	Pci/l	· · · · · · · · · · · · · · · · · · ·	-(1)	-	
Alkalinity, Max	mg/l	 148.9	200(600)	_	
Aluminum(as Al), Max	mg/l	BDL	0.03(0.2)	-	,
Boron,Max	mg/l	BDL	1(5)		

Date: April 2017 Location: BP CC-66 (Underground)

Item	Unit	Measure d Value (Mean)	Measured Value (Max.)	Country's Standards	Referred Internation al Standards	Remarks (Measurem ent Point, Frequency, Method, etc.)
Color,Hazen units,Max			Colourless	5(25)	-	20 locations Once/6
Odour	-		Unobjectio nable	Unobjection able	-	months
Taste	-		Agreeable	Agreeable	-	During
Turbidity,NTU, Max	-		1.54	5(10)	-	entire çivil construction
pH Value	-		7 .78	6.5-8.5	-	stage or
Total Hardness (as CaCO₃), Max	mg/l		129.6	300(600)	-	even later, if directed by DMRC

Iron(as Fe) ,max	mg/l		0.07	0.3(1.0)	-	
Chloride(as CI), Max	mg/l		59	250(1000)	-	
Residual free Chlorine, Min	mg/l		.18	0.2	-	
Fluoride(as F), Max	mg/l		1.27	1.0(1.5)	-	
Dissolved solids, Max	mg/l		657	500(2000)		
Calcium(as Ca), Max	mg/l			75(200)	_	
Magnesium(as Mg), Max	mg/l			30(100)	-	
Copper(as Cu), Max	mg/l		BDL	0.05(1.5)	□	
Manganese(as Mn), Max	mg/l		BDL	0.1(0.3)	-	
Sulphate(as \$O₄), Max	mg/l		47	200(400)	<u>-</u>	
Nitrate(as NO₂), Max	mg/l		17.4	45(100)	-	
Phenolic compounds (as	mg/l		BDL	0.001(0.002)	-	
C ₆ H ₅ OH),Max Mercury(as Hg), Max	mg/l		BDL	0.001	-	
Cadmium(as Cd), Max	mg/l		BDL	0.01	-	,
Selenium(as Se), Max	mg/l		BDL	0.01	-	
Arsenic(as As), Max	mg/l		BDL.	0.05	-	
Cyanide(as CN), Max	mg/l		BDL	0.05	-	
Lead(as Pb), Max	mg/l		BDL	0.05	-	
Zinc(as Zn), Max	mg/l		.69	5(15)	-	
Anionic Detergents (as MBAS),Max	mg/l			0.2(1.0)		
Chromium (as Cr6⁺),Max	mg/l	, 	BDL	0.05	-	
Polynuclear aromatic	mg/l		BDL		-	
· 						

Attachment 2

							k retac
hydrocarbons(as PAH),Max							
					· · · · · · · · · · · · · · · · · · ·	-	. [
Mineral Oil	mg/l			0.01	-	_	ŀ
Pesticides, Max	mg/l			Absent	-		
Radioactive						Ť .	l
Materials, Max e) Alpha emitters	Bq/l			-(0.1)	-		
Radioactive Materials, Max f) Beta emitters	Pci/I	·		-(1)	-		
Alkalinity, Max	mg/l		109.4	200(600)	-	1	- 13
Aluminum(as			BDL		· · · · · · · · · · · · · · · · · · ·		[]
AI), Max	mg/l			0.03(0.2)	_		
Boron,Max	mg/l		BDL	1(5)	-		

Date

Date:						
ltem	Unit	Measure d Value (Mean)	Measured Value (Max.)	Country's Standards	Referred Internation al Standards	Remarks (Measurem ent Point, Frequency, Method, etc.)
Color, Hazen units, Max				5(25)	-	20 locations Once/6
Odour	-			Unobjection able	•	months
Taste	-			Agreeable		During
Turbidity,NTU, Max	-			5(10)	-	entire civil construction
pH Value	-			6.5-8.5	-	stage or
Total Hardness (as CaCO₃), Max	mg/l		·	300(600)	-	even later, if directed by DMRC
Iron(as Fe) ,max	mg/l			0.3(1.0)	-	
Chloride(as Cl), Max	mg/l			250(1000)	<u>.</u>	
Residual free Chlorine, Min	mg/l			0.2	-	
Fluoride(as F), Max	mg/l			1.0(1.5)	-	
Dissolved solids, Max	mg/l			500(2000)		
Calcium(as Ca), Max	mg/l			75(200)	-	
Magnesium(as Mg), Max	mg/l			30(100)	••	
Copper(as Cu), Max	mg/l			0.05(1.5)	-	; ;
Manganese(as Mn), Max	mg/l			0.1(0.3)	_	

Sulphate(as \$O ₄), Max	mg/l			200(400)	-		
Nitrate(as NO ₂), Max	mg/l			45(100)	-		,
Phenolic compounds (as C ₆ H ₅ OH),Max	mg/l			0.001(0.002)	-		
Mercury(as Hg), Max	mg/l			0.001	-		ï
Cadmium(as Cd), Max	mg/l			0.01	-	•	,
Selenium(as Se), Max	mg/l	,		0.01	-		
Arsenic(as As), Max	'mg/l			0.05	<u>.</u>		
Cyanide(ás CN), Max	mg/l			0.05	· -		
Lead(as Pb), Max	mg/l			0.05	-		
Zinc(as Zn), Max	mg/l		:	5(15)			
Anionic Detergents (as MBAS),Max	mg/l			0.2(1.0)	- .		
Chromium (as Cr6 ⁺),Max	mg/l			0.05	-		
Polynuclear aromatic hydrocarbons(as PAH),Max	mg/l			-	-		
Mineral Oil	mg/l			0.01			
Pesticides, Max	mg/l			Absent	-		
Radioactive Materials, Max g) Alpha emitters	Bq/l			-(0.1)	-	• ,	
Radioactive Materials, Max h) Beta emitters	Pci/l			-(1)	- -		
Alkalinity, Max	mg/l			200(600)	# ************************************		
Aluminum(as Al), Max	mg/l			0.03(0.2)	-		•
Boron,Max	mg/l			1(5)	-	Control of the Contro	,

Noise / Vibration

Date: April 2017

Location: CC-04 (Azadpur) (Underground)

Item	Unit	Measured Value (L _{eq})	Meas ured Value (L _{Max})	Country's Standards (Environmental Management Manual by DMRC)	Occupancy	Remarks (Measure ment Point, Frequen cy, Method,
Noise level (Leq) and Lmax	dB(A)	Rameshwar Leq(day) – 69.3 Leq(night)–55.2 Lmin- 52.2 Azadpur Leq(day)- 67.2 Leq(night)–60.3 Lmin- 53.8	73.6	National Standards Area Leg(d) Leg(n) Resi 55 45 Comm 65 55 Indstl 75 70 Silence 50 40 DMRC Env Manual (when pre construction levels	Çommerçi	etc.) 30locatio ns 24hours/ti me Once/we ek During entire civil constructi on stage or even later, if directed by DMRC
				are not known) Resi Lmax Daytime: 75 Nighttime: 65 Comm & and Indstl At all time: 85	al / residence	
Vibration level	RM\$ (mm/s)			in good condition:25 in fair condition:12 in poor condition:5 Water supply Structures:5 Heritage structure/ Bridge structures:5	·	10locations 24hours/time 24hours/time Once/week During entire civil construction stage or even later, if directed by DMRC

Date: May 2017

3

Location: CC-79 (Okhla Phase-III) (Elevated)

Item	Unit	Measured Value (L _{eq})	Meas ured Value (L _{Max})	Country's Standards (Environmental Management Manual by DMRC)	Occupancy	Remarks (Measure- ment Point, Frequenc y, Method, etc.)
Noise level (Leq) and Lmax	dB(A)	Activity Area Leq(Day)-71.2 Leq(night)-63.9 Lmin- 43.0 Batching Plant Leq(Day) - 68.0 Leq(night)-62.1 Lmin - 43.5	85.6 85.3	National Standards Area Leg(d) Leg(n) Resi 55 45 Comm 65 55 Indstl 75 70 Silence 50 40		30location s 24hours/ti me Once/wee k During entire civil constructio n stage or
				DMRC Env Manual (when pre construction levels are not known) Resi Lmax Daytime: 75 Nighttime: 65 Comm & and Indstl At all time: 85	Commerci al / residence	even later, if directed by DMRC
Vibration level	RMS (mm/s)			Structures in good condition:25 in fair condition:12 in poor condition:5 Water supply Structures:5 Heritage structure/ Bridge structures:5	-	10location s 24hours/ti me Once/wee k During entire civil constructio n stage or even later, if directed by DMRC

Date: April 2017

Location: CC-43(MIE- City Park) (Elevated)

	T- (ĺ	Remarks
1	• •	Measured	Meas	Country's	Occupancy	(Measure-
	I I m i 4		ured	Standards		ment
ltem	Unit	Value (L _{eq})	Value	(Environmental		Point,
	ļ		_	Management		Frequency
		•	(L _{Max})	Manual by		, Method,
				DMRC)		etc.)
						30locations
Noise	:	Casting Yard		National		24hours/tim
level		Leq(Day) - 73.1		<u>Standards</u>		
(Leq)	₫₿(A)	Leq(night)-65.3	80.8	Area Leg(d)		ę
and		Lmin - 42.1		<u>Leq(n)</u>	1	Once/week
Lmax	,			Resi 55		_
4	1	Bus Stand		45		During
1		Leq (day) - 72.9	85.2	Comm 65		entire civil
		Leq(Night)-63.7		55		constructio
. [Lmin – 46.5		Indstl 75		n stage or
				70		even later,
		City Park		Silence 50		if directed
	ļ	Leg(Day) - 68.4	81.7	40		by DMRC
			01.7	1 40		7, "
	į	Leq(Night)-60.5		DMRCEnv Manual	Commerçi	
		Lmin – 43.2		(when pre	al/	
		 	00.0	construction levels	residence	
		MIE	82.8			
		Leq (Day)- 71.5		are not known)		
		Leq(Night)-63.4		Resi		
		Lmin – 51.6		Lmax		
			•	Daytime:		
				75		
		, .		Nighttime:		i .
				65		
		,		Comm & and		
				Indstl		
į.				At all time:		
				85		
	Ì	•				
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			 	Structures	· · · · · · · · · · · · · · · · · · ·	10locations
Vibration	RMS	•				24hours/tim
level	(mm/s)	,	†			e
				condition:25		Once/week
			ŀ			\$1,000 HYOK
		·		condition:12		During
	ļ			in poor		entire çivil
			}	condition:5		· · · · · · · · · · · · · · · · · · ·
]]		Water supply		constructio
		•		Structures:5		n stage or
			1	Heritage structure/		even later,
	Į.			Bridge		if directed
				structures:5	<u> </u>	by DMRC
l	!	1		Land Table Control of the control of	/, / / / /	11 Ch. 1 C. 1 Chin 12 A. 12 C. 12 A. 1.

Location: CC-34 (Janakpuri-Dabri mod) (Underground)

Date: May 2017

Item	Unit	Measured Value (L _{eq})	Meas ured Value (L _{Max})	Country's Standards (Environmental Management Manual by DMRC)	Occupancy	Remarks (Measure- ment Point, Frequency, Method, etc.)
Noise level (Leq) and Lmax	dB(A)	Janakpuri Leq (Day)- 66.8 Leq(night)-60.7 Lmin- 42.4 Dabri mod Leq(Day) — 68.5 Leq(night)-61.2 Lmin – 47.3	80.6 80.3	National Standards Area Leq(d) Leq(n) 55 45 65 Comm 65 55 Indstl 75 70 Silence 50 40 50		30locations 24hours/tim e Once/week During entire civil constructio n stage or even later, if directed by
		Dasrathpuri Leq(Day) – 70.2 Leq(night)-60.8 Lmin – 45.8	83.0	DMRC Env Manual (when pre construction levels are not known) Resi Lmax Daytime: 75 Nighttime: 65 Comm & and Indstl At all time: 85	Commerci al / residence	DMRC
Vibration level	RMS (mm/s)			Structures in good condition:25 in fair condition:12 in poor condition:5 Water supply Structures:5 Heritage structure/ Bridge structures:5		10locations 24hours/tim e Once/week During entire civil constructio n stage or even later, if directed by DMRC

Excavated soil (Leaching test)

Date: April,2017

Location: Ramp Area ÇC-66

ltem	Unit	Measured Value (Mean)	Country's Standards	Referred International Standards	Remarks (Measurement Point, Frequency, Method, etc.)
Mercury(as Hg)	mg/l	ND	-	0.0005	In each Underground
Cadmium(as Cd)	mg/l	ND	-	0.01	Construction Contract
Arsenic(as As)	mg/l	ND	-	0.01	Once/6months During entire
Cyanide(as CN)	mg/l	ND	-	Not detected	civil construction stage Samples should
Lead(as Pb)	mg/l	ND	-	0.01	be taken from the underground
Chromium(as Cr6 ⁺)	mg/l	ND	-	0.05	lowest point.

Date:

Location:

ltem ,	Ųnit	Measured Value (Mean)	Country's Standards	Referred International Standards	Remarks (Measurement Point, Frequency, Method, etc.)
Mercury(as Hg)	mg/l		<u>.</u>	0.0005	In each Underground
Cadmium(as Cd)	mg/l			0.01	Construction Contract Once/6months
Arsenic(as As)	mg/l		-	0.01	During entire
Cyanide(as CN)	mg/l		=	Not detected	stage Samples should
Lead(as Pb)	mg/l			0.01	be taken from the underground
Chromium(as Cr6 ⁺)	mg/l	·	_	0.05	lowest point.

Excavated soil (Amount)

Date:

#n n n n n n n n n

Line	Excavated Amou Approx.('000 m³)	Name of Disposed Site	Disposed Amount Approx.('000 m3)
Line-2			:
Line-6*			
Line-7*			

Atta			2

				<u>r</u>	
		, , , , , , , , , , , , , , , , , , , ,	 	 	* 4- 4944 H P - 1
Line-8*		• • •			

Ecological Monitoring (Flora Monitoring)

CPM	Permission to fell trees	No. of trees actually felled	No of trees planted	No of trees transplanted	Location of plantation
CPM-1	Nil	Nil	Nil	Nil	
CPM-2				•	
CPM-3		7			
CPM-4	Nil	· Nil	Nil	Nil	
CPM-5	Nil	Nil	10	Nil	Palam Station
CPM-6					-
CPM-7	Nil	Nil	Nil	Nil	
CPM-8	Nil	Nil	Nil	Nil	
CPM-9				, ,	
CPM-1Q	513	Nil	Nil	Nil	
ED/Tech					

^{*} The data collection for soil excavation & tree cutting is under process and complete details will be provided in next report.

2.2 During Operation

Air Quality (Ambient Air Quality)

Date 1

Location:

ltem	Unit	Measured Value (Mean)	Measured Value (Max.)	Country's Standards	Referred International Standards	Remarks (Measurement Point, Frequency, Method, etc.)
PM ₁₀	µg/m³			100 (24hours) (CPCB)	IS 5182 (Part 23)	48hours/time Once/month For 3 years

Effluent at Depot

Date:

Location:

· Item	Unit	Va	sured lue ean) Outl	Measur ed Value (Max.)	Country's Standards	Referred Internation al Standards	Remarks (Measureme nt Point, Frequency, Method, etc.)
рН	-			- <u>-</u>	5.5-9.0	_	(Depot)
TSS	mg/l			-	100 .	-	Once/4mont
BOD	mg/l	,	·	-	30	_	hs
COD	mg/l			-	250	-	For 3 years
Oil/Grease	mg/l			-	10	-	

Ground Water Quality (Drinking Water Quality: IS 10500:1991)

Date:

Location:

ltem	Unit	Measured Value (Mean)	Measure d Value (Max.)	Country's Standards	Ref erre d Inte rnat ion al Sta nda rds	Remarks (Measurement Point, Frequency, Method, etc.)
Color,Hazen units,Max	-		· •	5(25)	1	(Depot)
Odour	-			Unobjectionab le	•	Once/year
Taste	-		· -	Agreeable		For 3years
Turbidity,NTU,M ax	-		-	-	-	
pH Value	-	,	_	6.5-8.5	-	
Total Hardness (as CaCO ₃),	mg/l	,	-	300(600)	-	·

Attachment 2

May		~ _ ~ ~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	 	· · · · · · · · · · · · · · · · · · ·	····		Attachment 2
Max Iron(as Fe) ,ma	v má/	<u> </u>		0.2(4.6)			the manufacturing and beautiful
Chloride(as Cl)	x mg/ mg/	1		0.3(1.0) 250(1000)	-	-	
Residual free Chlorine, Min	mg/l		-	0.2		7	•
Fluoride(as F), Max	mg/l		-	1.0(1.5)	-		1
Dissolved solids, Max	mg/l			500(2000)	-		
Calcium(as Ca), Max	mg/l		-	75(200)	-	- 	
Magnesium(as Mg), Max	mg/l			30(100)	-		
Copper(as Cu), Max	mg/l		_	0.05(1.5)	-	֓֟֟ <u>֚</u>	
Manganese(as Mn), Max	mg/l		-	0.1(0.3)	_		
Sulphate(as SO₄), Max	mg/l		-	200(400)	-		
Nitrate(as NO₂), Max	mg/l		-	45(100)	_		
Phenolic compounds (as C ₆ H ₅ OH),Max	mg/l		-	0.001(0.002)	-		
Mercury(as Hg), Max	mg/l		-	0.001	-		·
Cadmium(as Cd), Max	mg/l		-	0.01	-		
Selenium(as Se), Max	mg/l		-	Q.Q1 .	_		
Arsenic(as As), Max	mg/l		-	0.05	-		
Cyanide(as CN), Max	mg/l		-	0.05	-		
Lead(as Pb), Max	mg/l		-	0.05	-		
Zinc(as Zn), Max	mg/i		, - .	5(15)			
Anionic Detergents (as MBAS),Max	mg/l		_•	0.2(1.0)	-		
Chromium (as Cr6⁺),Max	mg/l		•	0.05	-	•	
Polynuclear aromatic hydrocarbons(a s PAH),Max	mg/l		~.	-	-		
	mg/l		-	0.01	-		1
Pesticides, Max	mg/l		_	Absent	-		
Radioactive Materials, Max	Bq/I		-	-(0.1)	-		

PPPPPPPPPPPPPPPPPPPPPPP

Attachment 2 Alpha emitters Radioactive Materials, Max Pçi/l Beta emitters 200(600) Alkalinity, Max mg/l Aluminum(as 0.03(0.2) Al), mg/l Max 1(5) Boron, Max mg/l

Noise / Vibration

Date:

アファファファファブラファファ

Location:

ltem	Unit	Measured Value (Mean)	Measured Value (Max.)	Country's Standards	Referred International Standards	Remarks (Measure- ment Point, Frequency, Method, etc.)
				Aer Son Son		
Noise level	dB				[Railway Noise] Daytime- 60 Night time- 55	15 Location 24 hours Once in a year at sensitive receptors along the elevated section from train operation

Date:

Location:

Item	Unit	Measured Value (Mean)	Measured Value (Max.)	Country's Standards	Referred International Standards	Remarks (Measure- ment Point, Frequency, Method, etc.)
------	------	-----------------------------	-----------------------------	------------------------	--	--

		,		Attachment 2 As and when
Vibration level	mm/s		FTA standard	As and when compliant arises.
•				\$*************************************
	,	 ·		·

Ecological Monitoring (Bird Strike near Okhla Bird Sanctuary)

Date: Location:

Duration: From / / to / /

クククククククククククククク

りまりりつうつうりゃ

	ltem	Number of Interviews with Train Operators who reported the accident during monitoring period	Number of Accidents Reported during the monitoring period	Name of Species lost in the accident	Remarks (Place of accident, frequency, Method, etc.)
_	Train Accidents involving bird fatality		,		4times/year For 2years Visual observation (If no
		•			bird hit is reported in this duration, then this monitoring may be discontinued, else it will continue). From the beginning, DMRC will instruct its train operator to compulsorily blow the horn while on the bridge across the Yamuna.

JICA Reply (Jan-Mar, 2017)

Air Monitoring

Location	NAAQS PM ₁₀ (Unit µg/m³)	Baseline data PM ₁₀ (Unit µg/m³)	Monitoring Results	Remarks, If any
Lajpat Nagar			197	
Sarai Kale Khan		Į Į	210	
Nizamuddin	1	169	215	
Ashram			212	
Vinobapuri			204	
MIA			367	•
Ghevra		1 .	319	
Tikri Kalan		1	385	
Tikri Border	100	No Monitoring	357	
Johri Enclave	1	. [274	
Shiv vihar	1		284	
CC-41 casting yard	1 .		315	
Naraina			194	
Mayapuri	1		208	
BRO	1	242	198	
Batching Plant CC-20			189	

Reason for high values:

すりりゅうりゅうりゅ

- 1. The results are from monitoring conducted in winter season. In winter season, the air pollution in Delhi-NCR is at its worst and for this reason; the supreme court of India has mandated the EPCA (Environment Pollution Control Authority) to come up with a Graded Action Response Plan.
- 2. The reasons of air pollution in Delhi are beyond the control of citizens of Delhi though vehicular and other pollution aspects are contributing to it.
- 3. The main reason of air pollution is crop & stubble burning in North Indian states especially in Punjab, Haryana and Uttarpradesh. Delhi being on the downwind area has to bear the pollution burnt entering in to the Delhi region.
- 4. Low Wind velocity and thermal inversion during winter agglomerate the problem.

Measures Taken:

Since the values were higher than NAAQS Standard, In addition to EPCA suggested measures, DMRC issued advisory to the contractor to reduce air pollution.

Noise Reply

Location	Area/ Zone	Area/ Zone CPCB Lir (dBA)		Monitor (dBA)	Remarks, If any	
		Day	Night	Leq (day)	Leq(night	
Sarai Kale Khan	Commercial	65	55	68.4	57.4	

Nizamuddin	Commercial	65	55	66.4	54.3	
MIA	industrial	75	70	71.3	62.6	
Ghevra	Commercial	65	55	67.9	63.1	· · · · · · · · · · · · · · · · · · ·
Tikri Kalan	Commercial	65	55	68.4	62.8	
Tikri Border	Commercial	65	55	70.4	66.9	
Mundka Casting Yard	Industrial :	75	65	70.2	62.6	The state of the s
Johri Enclave	Commercial	65	55	76.3	65.7	
Shiv vihar	Commercial	65	55	71.4	65.9	
CC-41 casting yard (GTB)	Residential	55	45	68	62.8	
Mayapuri	Residential	55	45	69.4	58.7	
BRO	Silent	50	40	67.2	56.8	
Batching Plant CC-20	Residential	55	45	70.6	59.3	

^{*}Bold indicates the values are higher than the national standard

Reason for higher values:

 Most of the elevated stations are being constructed on above or by the side of busy roads such as Ring Road, National highways and State highways. Therefore, at these locations the ambient noise due to high traffic movement is already higher than the national standards.

Measures taken:

ラクラクラクラクラクラファウゥ ラクラファクラファウァ

Following are some of the steps taken for the comfort of receptors:

- 1. Noise barriers have been installed at most of the sites which are nearby residential colonies.
- 2. Noise generating activities are planned such that two heavy noise generating activities should not carry out simultaneously.
- 3. DG sets at site have been provided with acoustic enclosures.

Ground Water Monitoring

Location	Monitoring results		Standards Value	Remarks, if any	
	Partcular	value	Value	_	
Şarita Vihar	Fluroide	3.56	1(1.5)		
	Nitrate	55.2	45(100)		
Shakarpur	Taste	Disagreeable	Agreeable	Ground Water is not used for drinking purpose here	

Reason:

1. In this location, baseline monitoring was not carried out at the site earlier due to land issues. Although Construction activities are not a cause of fluoride discharge that would have discharged into ground water. Hence, this can be considered as characteristic of that aquifer from where sample has been taken.